

P&I SUPPLY

STOP THE DROP

ON-SITE, MOBILE TETHER STATION

What is a Tool Tethering Station?

This innovative tethering station set will provide the site with a one stop shop for tethering tools. An employee, expertly trained in tool tethering by a P&I expert, will man the station and tether tools for anyone on site. Simply keep the station stocked with the appropriate product and lock it up when not in use.




STORAGEMASTER
KNAACK MODEL 49



JOBMASTER
KNAACK MODEL 129



Each Tool Tethering Station comes custom and fully stocked with tools **A**, guides **B** and a scale **C** to ensure better drop protection for your work site.



What are the benefits?

Turnkey Design: Ready to go when it hits the jobsite.

Convenient: Keep it stocked and tether any tools on the spot.

Easy-to-Use: Labels indicate appropriate attachments and tethers.

Step-by-Step Instructions: Tether guides and posters included.

Efficient: Time saving.

Everything Included: Digital scale for weighing tools.

Mobile: Strategically place anywhere on the site—no more walking to the tool room to tether your tools.

Innovative: These are the future of tethering on a jobsite.

Secured: Lockable and weatherproof.

How does a Tool Tethering Station work? Flip the sheet.

TOOL TETHERING SYSTEM

Each Tool Tethering Mobile Station includes an easy, 4-step guide to safely tether tools. The process only takes a few minutes. An introduction is included below.

1 Weigh the Tool.

Each station includes a scale for weighing tools up to 50lbs.



2 Select an Attachment Point.

Attachments vary depending on tool weight and size. If the tool already has a manufactured tether point (tether-ready), you can proceed to STEP 4. If it does not, choose the appropriate attachment point.




1 lb or less
Quick Spin



2 lbs or less
Quick Ring



5 lbs or less
D-ring



35 lbs or less
Tool Cinch

3 Secure the Attachment Point to the Tool.

If using the d-ring or the tool cinch, you **MUST** wrap the tape 10-12 times over the attachment point.



4 Connect the Lanyard.

Choose appropriate lanyard and connect to attachment point.



5 lbs or less



10 lbs or less



35 lbs or less



80 lbs or less



Following completion of this 4-step process, the tool is now safely tethered and ready to be used at heights.

Remember if the tool is over 5 lbs, it cannot be anchored to your person. You **MUST** find a fixed anchor point.

For more details regarding the P&I Supply Tool Tethering Station and all your safety needs, contact:

Mark Eldersveld, Safety Specialist
(616) 481-1354 | meldersveld@pisupply.com